


Keynotes:

- Profile for oiled or stained weatherboards only.
- All nail fixings pre-drilled min. 1mm diameter smaller than the nail gauge.
- All NZ NATURAL TIMBER CO Ltd timber products to be pre-coated and cut ends and edges and all fresh cut surfaces double coated and sealed before fixing. All timbers are to be coated as per Dryden 's specification.
- Profiles as per NZS 3617, Branz Bulletin 411, and/or compliance achieved through in-service history, length of service not less than 15 years in all NZ environments B2/VM1 1.1.1 (a).
- Timber to comply with NZBC B2 Durability B2.3.1 (b).
- Profiles shall be fixed in accordance with E2/AS1 Table 24.



ST102 D4S Mouldings and Facings

- Finish:**
- DF/S (Dressed face sanded)
 - BSF (or Band sawn finish sanded/denibbed)
 - Dressed face pre-coated boards must be face sanded prior to coating.

Address: 68 /10 Marsden Bay Drive, Marsden Cove, Northland Phone: 0800 NATIVE Email: sales@nznaturaltimber.co.nz Website: www.sales@nznaturaltimber.co.nz	Drawing ST102 Scale 1 : 2 at A4	Title 65x20mm Profile Date 16-10-2025	NZ NATURAL TIMBER COMPANY
---	---	---	---